



## Counter-Top Filtered Water Dispenser

### CT-868A

- ◆ Hot / Chilled / Ambient Water
- ◆ Touch Control Panel
- ◆ Water Leak Detection & Shut-off Control
- ◆ Built-in Pop up Cup Dispenser
- ◆ LED Night Lights
- ◆ High Dispensing Gap
- ◆ Chilled Glasses/Hour: 100
- ◆ Heating Cups/Hour: 72

Available Option: -

- ◆ Ambient / Chilled / Soda Water
- ◆ Reverse Osmosis or Nano Filtration



(W) 320 × (D) 350 × (H) 480 mm



Available Color



**TÜV**  
AUSTRIA

CE

**DOW**

**NSF**

 **Aqua  
Vital**  
Purified for life-

[www.aqua-vital.com.hk](http://www.aqua-vital.com.hk)

## Features:

- ❑ Hot, Chilled & Ambient Water
- ❑ Touch Control Panel
- ❑ Water Leakage Detection and Automatic Shut-off Control
- ❑ ABS Casing, Anti-Scratch and Durable
- ❑ Build-in Pop Up Cup Dispenser
- ❑ LED Lighting on Dispensing Place
- ❑ High Dispensing Gap for Getting Water Easily
- ❑ Automatic Water Inflow and Shut-off Control
- ❑ Hot Water Safety Lock
- ❑ Automatic Heating Shut-off when hot water tank is empty
- ❑ Saving Energy: Individual On/Off Switch for Boiling & Chilling
- ❑ Hot Water Re-boiling Function
- ❑ UV Sterilization System
- ❑ SGS Tested Water Filtration System (Refer to Removal Performance Report)



**Made In Taiwan**



Aqua Vital Water Filtration Systems Ltd  
www.aqua-vital.com.hk Tel: (852) 3565 1333

## Specifications of CT-868A

### Dimension

(W) 320 x (D) 350 x (H) 480 mm (±5mm)

### Power Rating:

Voltage : 220-240V 50Hz

Heating Power : 500W

Chilling Power : 100W

### Idle Mode:

On Mode with No Water Draw :  $\leq 0.85$  kWh/day\*\*

\*\* Tested According to Energy-Efficiency Criteria for ENERGY STAR by the Supplier

### Water temperatures:

Chilled 4°C-10°C

Hot 88°C -94°C

Default set at 5°C

Default set at 94°C

### Recovery Rate:

Hot 12 L/Hour

Chilled 20 L/Hour

### Water Tank Capacity:

Hot 2 L

Chilled 4 L

Ambient Direct-Flow (10 L for RO)

### Filtration System:

NF/ 4-Stage Filters Nano Filtration (NSF 42 & 53 Compliance)

- ① Sediment Pre-Filter / 5 Microns
- ② KX Carbon Block Filter / MMF-2710-F1-CBR
- ③ Hollow Fiber Membrane / 0.01 Micron
- ④ GAC Carbon Post Filter

### Water Production Rate:

2 Liters per Minute

### Water Pressure:

40 - 80psi

### UV Sterilizer (Optional)

Philips TUV G6T5

### (Optional)

RO/ 5-Stage Reverse Osmosis Purification (NSF 58 Compliance)

- ① Sediment Pre-Filter / 5 Microns
- ② GAC Carbon Pre-Filter
- ③ Sediment Filter / 1 Micron
- ④ R.O. Membrane (Dow FILMTEC) TW30-1812-75 GPD
- ⑤ GAC Carbon Post Filter

### Water Production Rate:

290 Liters per Day

### Water Pressure:

30 - 80psi

