

# Reverse Osmosis Purified Water Dispenser



(W) 40 x (D) 33 x (H) 105 cm

## RO-939H

Hot, Chilled & Ambient Water  
Reverse Osmosis Water Purification System  
Water Leak Detection & Shut-off Control

- ◆ Automatic Water Inlet /Shut-off
- ◆ Individual On/Off Switch for Boiling & Chilling
- ◆ John Guest Quick Connect Fittings
- ◆ LG Compressor Cooling
- ◆ Tempered ABS Casing

SPECIFICATIONS	Filtration Type	
	Purification	Gallon / Day
5-Stage Filters	( 1 )	Pre-filter / PP 5μ
	( 2 )	GAC Carbon
	( 3 )	Sediment
	( 4 )	FILMTEC RO Membrane
	( 5 )	Post Carbon
Water Temperature	Hot	100°C
	Chilled	4 - 10°C
Recovery Rate	Hot	12 L / Hour
	Chilled	20 L / Hour
Working Pressure	Minimum	30 psi
	Maximum	100 psi
Dimension	(W) 40 x (D) 33 x (H) 105 cm	
Inlet Tube	3/8"	
Drainage	1/4"	
Rated Voltage	AC 220 - 240, 50 Hz	
Weight	Gross	
	18 kg	



WHC NETCONN (HONG KONG) LTD

Unit 607, 6 Floor, Yen Sheng Centre, 64 Hoi Yuen Rd., Kwun Tong, Kowloon  
Tel: (852) 3565 1333 Fax: (852) 3565 1666

[www.WaterHealthCare.com.hk](http://www.WaterHealthCare.com.hk)