

NF2 Nano-Filtration Water System



Spun Polypropylene Sediment Pre-Filter
Screens out dirt, rust and micro-particles
Particulate Reduction Class II

AquaVital

Pressure: 20-80 psi
Temperature: 4-20°C (33-100°F)
Flow Rate: 3.0 L/min
Standard Micron Rating: 5
Service Life: To be replaced every 6 months or if a noticeable reduction in flow occurs.

NSF/ANSI Standard 42 and 53 Compliance

Warning: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

AquaVital is the trademark of WMC Systems (HK) Ltd
NF2 is a trademark of NSF International
Made by Mem Filter Co. Ltd., Korea

Aqua Vital
Purified for life™

Granular Activated Carbon Pre-Filter
Removes chlorine, THMs, pesticides and volatile organic compound (VOC)

AquaVital

Pressure: 20-80 psi
Temperature: 4-20°C (33-100°F)
Flow Rate: 3.0 L/min
Standard Micron Rating: 20
Service Life: To be replaced every 6 months or if a noticeable reduction in flow occurs.

NSF/ANSI Standard 42 and 53 Compliance

Warning: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

AquaVital is the trademark of WMC Systems (HK) Ltd
NF2 is a trademark of NSF International
Made by Mem Filter Co. Ltd., Korea

Aqua Vital
Purified for life™

Hollow Fiber Membrane Filter NF

AquaVital

Pressure: 14-57 psi
Temperature: 4-20°C (33-100°F)
Flow Rate: 1.0 L/min
Standard Micron Rating: 1000
Service Life: To be replaced every 12 months or if a noticeable reduction in flow occurs.

NSF/ANSI Standard 42 and 53 Compliance

Warning: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

AquaVital is the trademark of WMC Systems (HK) Ltd
NF2 is a trademark of NSF International
Made by Mem Filter Co. Ltd., Korea

Aqua Vital
Purified for life™

Granular Activated Carbon Post Filter
Removes odor and improves taste

AquaVital

Pressure: 20-80 psi
Temperature: 4-20°C (33-100°F)
Flow Rate: 3.0 L/min
Standard Micron Rating: 20
Service Life: To be replaced every 12 months or if a noticeable reduction in flow occurs.

NSF/ANSI Standard 42 and 53 Compliance

Warning: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

AquaVital is the trademark of WMC Systems (HK) Ltd
NF2 is a trademark of NSF International
Made by Mem Filter Co. Ltd., Korea

Aqua Vital
Purified for life™



Aqua Vital Water Filtration Systems Ltd
www.aqua-vital.com.hk Tel: (852) 3565 1333

NF2 Nano-Filtration Water System

NF2 designed for system of built-in for our filtered water dispensers



NF2 Nano-Filtration Water System

- 4-Stage High Efficient Nano-Filtration System
- Filtration Accuracy up to **0.01 Micron**
- Compact and Slim Design, Counter-top or Under-sink Mounted
- No Electricity required for Operation
- Patented "Twist to Install" for Quick & Easy Filter Replacement
- **SGS** Tested Removal of **Pathogenic Bacteria & Lead***
- **NSF 42 & 53** Compliant



4-Stage Filters

1. Sediment Pre-Filter (5 Microns)
2. KX CTO Pre-Carbon Filter
3. Hollow Fibre Membrane (0.01 Micron)
4. CALGON Post Activated Carbon Filter



NF2 Nano-Filtration Water System

Functions of 4-Stage Filtration System:

1. Screens out mud and micro-particles
Particulate Reduction Class II
2. Reduction of Chlorine, Scale Organics,
Lead and Mercury
3. Eliminates Bacteria, Cyst, Colloid and Rust
4. Removes odor and improves taste

*100% Removal Rate of Bacteria

*Lead Removal Rate over 99.7%

Specification:

- Dimension : (W) 280 x (D) 100 x (H) 300 mm
- Temperature: 4 - 38°C
- Micron Rating: 0.01 Micron (μm)
- Water Output Rate: 2 Liters / Minute
- Water Pressure: 20 - 80 psi